


111-85119

Article Number: 111-85119



Description: Identification Tie, 8" Long, 50lb Tensile Strength, PA66, Natural, 50/pkg

Base Data	Local Order Number	IT50RT9K2
	Type	IT50RT
	Color	Natural (NA)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Identification plate feature allows bundles to be easily marked and identified.</li> <li>• Wire and cable harnesses can be secured and identified using just one product, which saves time.</li> <li>• Plates can be marked manually with a permanent marker or with a pre-printed adhesive label.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton Identification cable ties feature an identification plate allowing wire and cable bundles to be easily marked and identified. These ties enable wire and cables to be secured and identified using just one product, saving installation time. The plates can be marked using a permanent marker or with a HellermannTyton adhesive label.
	Short Description	Identification Tie, 8" Long, 50lb Tensile Strength, PA66, Natural, 50/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		225.0N
Length L (Imperial)		8.0"
Length L (Metric)		205.0mm
Fixation Method		None
Identification Plate Position		attached to bundle
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		1.8"
Width W (Metric)		46.0mm
Width W2 (Imperial)		0.19"
Width W2 (Metric)		4.7mm
Height H (Imperial)		1.04"

111-85119



Product Dimensions	Height H (Metric)	26.3mm
	Height of printable area (metric)	46.0mm
	Bundle Diameter Min. (Imperial)	0.4"
	Bundle Diameter Min. (Metric)	10.0mm
	Bundle Diameter Max. (Imperial)	1.7"
	Bundle Diameter Max. (Metric)	44.0mm
	Outside Diameter Min. (Imperial)	0.393"
	Outside Diameter Min. (Metric)	10.00mm
	Outside Diameter Max. (Imperial)	1.73"
	Outside Diameter Max. (Metric)	44.00mm
	Thickness T (Imperial)	0.05"
	Thickness T (Metric)	1.2
	Width of printable area (metric)	26.30mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	US MILSPEC	MS3368-4-9D
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	Certification/Specification	MS3368
UL Recognized (US and Canada)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	2.5kg